


LASAK BioniQ QR Exocad library structure



Scanbody QR,
indexed – long
Ref. No. 2815.00



Connection type

QR/I

QR/NI

QR/B

Application

Solo crown

Linear bridge

Bridge

Ref. No. 2858.00




S3.5
S4.0
T4.0
S5.0
T5.0

Specification		L0.7	L1.5	L2.5	L3.5	Compatible burn-out coping
QR/I/d4.5/h5.5, indexed – wide		2218.07	2218.15	2218.25	2218.35	B (d4.5)
QR/I/d4.5/h8.0, indexed – wide		2225.07	2225.15	2225.25		B (d4.5)
QR/I/d4.5/h3.5, indexed – wide		2230.07	2230.15	2230.25		B (d4.5)
QR/I/d3.8/h5.5, indexed – narrow		2216.07	2216.15	2216.25		A (d3.8)
QR/NI/d4.5/h5.5, non-indexed – wide		2220.07	2220.15	2220.25		B (d4.5)
QR/B/d4.5/h5.5/B, bridge – wide		2221.07	2221.15	2221.25		B (d4.5)
QR/B/d4.5/h3.5/B, bridge – wide			2234.15	2234.25		B (d4.5)

LASAK BioniQ QN Exocad library structure



Scanbody QN,
indexed – long
Ref. No. 2840.00



Connection type

QN/I 

QN/NI 

Application



Solo crown

Linear bridge

Ref. No. 2859.00



S2.9

Specification		L0.7	L1.5	L2.5	L3.5	Compatible burn-out coping
QN/I/d3.8/h5.5, indexed – narrow		2208.07	2208.15	2208.25	2208.35	A (d3.8)
QN/NI/d4.5/h5.5, non-indexed – wide			2213.15	2213.25		B (d4.5)