


### LASAK BioniQ QR Exocad library structure



Scanbody QR,  
indexed – solo  
Ref. No. 2881.00



Connection type

QR/I 

Application





Solo crown



Ref. No. 2858.00




S3.5  
S4.0  
T4.0  
S5.0  
T5.0

Specification		L0.7	L1.5	L2.5	L3.5	Compatible burn-out coping
QR/I/d4.5/h5.5, indexed – wide		2218.07	2218.15	2218.25	2218.35	B (d4.5)
QR/I/d4.5/h8.0, indexed – wide		2225.07	2225.15	2225.25		B (d4.5)
QR/I/d4.5/h3.5, indexed – wide		2230.07	2230.15	2230.25		B (d4.5)
QR/I/d3.8/h5.5, indexed – narrow		2216.07	2216.15	2216.25		A (d3.8)

### LASAK BioniQ QN Exocad library structure



Scanbody QN,  
indexed - solo  
Ref. No. 2882.00



Connection type

QN/I 

Application

Solo crown

Ref. No. 2859.00



S2.9

Specification

QN/I/d3.8/h5.5, indexed - narrow



L0.7

2208.07

L1.5

2208.15

L2.5

2208.25

L3.5

2208.35

Compatible  
burn-out coping

A (d3.8)